5325

tapespec™

DOUBLE SIDED CLOTH CARRIER TAPE

DESCRIPTION:

The 5325 consists of a synthetic fabric cloth carrier coated both sides with a thick rubber adhesive. This tape conforms to rough surfaces and is water resistant, adhering to most surfaces. After short periods of use (Interior / Exterior) the 5325 can be removed cleanly from substrates such as wood (not polyurethane wood), plastic, metal and concrete.

Limited shear strength - not suited to holding heavy weights.

AREAS OF USE:

General fixing and holding applications, excellent on rough surfaces.

Sign and Display Market

* Suited to temporary attachment of posters, banners and signs (Real Estate Signs) in exterior conditions to wood (plywood), plastic, metal and concrete.
* (Not suitable for long term use when directly exposed to UV and extreme temperatures.)
* Excellent for the temporary securing of display and advertising products e.g. Securing glass display bottles, and adhering plastic corflute together

Note: Testing is always recommended on all surfaces before application (product suitability).

Entertainment & Carpet Industry

* The Double sided "Gaffers" tape used for holding and fixing applications on theatre and movie sets.
* Semi-Permanent holding down of needle punch carpet and carpet squares.

Note: Not suitable for PVC, polished marble or polyurethane wood surfaces

Note: Testing is always recommended on all surfaces before application (product suitability).

Please refer to our surface preparation guides - www.tapespec.co.nz

Concrete Precast Industry

* Used to hold profiles or the mould in place when they pour precast concrete for tilt slab buildings

Technical data*

Carrier:	**Synthetic fabric cloth**
Colour:	Cream
Thickness:	0.41mm
Adhesive:	**Natural Rubber**
Release Paper:	White silicone paper
Adhesion to Steel:	gf /24mm 1200
Tack:	Ball 40
Adhesion to plywood:	gf / 25mm 900
mortar	gf / 25mm 1320
carpet	gf / 25mm 1230
Shrink ratio (48 hrs)	kgf / 25mm '0.3
Service Temperature:	5 to 100 °C
Application Temperature:	5 to 30 °C
Shelf life:	12 months

Roll size	**Slit to the required width size x 25 metres**

Surface Preparation

The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 25°C

For detailed surface prep & application guides please refer to - www.tapespec.co.nz

*The statements in this information sheet are based upon our knowledge and practical experience. The data is intended only as a source of information, is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and application, customers should independently determine the suitability of this material for their specific purpose, prior to use.